
LG COMMERCIAL TV


INFORMATION DISPLAY AND SOLUTIONS














Contents

1. LG Commercial TV Highlights	06
2. LG Commercial TV Category	09
3. LG Commercial TV Introductions	
- Pro:Centric® Smart with OLED	10
- Pro:Centric® Smart	14
- Pro:Centric® V	18
- TV Signage (Commercial Lite)	22
- TV Signage (Smart TV Signage)	26
- Peripherals	28
- EU / CIS Line up	29
4. Specifications	30



LG COMMERCIAL TV HIGHLIGHTS



* Actual product may differ from the image.

OLED Technology & Design

LG commercial TV was created with a revolutionary OLED technology that redefined what was possible for display design and image quality. Direct light emission of OLED pixels obviated backlighting, allowing for an ultra-slim display. OLED pixels also display richer colors with vivid accuracy. LG developed the OLED Wallpaper based on this revolutionary technology, creating an ultra-thin panel that virtually does away with thickness altogether. It is no wallflower, the astounding wallpaper design is eye-catching in any space and setting.

UHD Resolution Models

UHD was once a novelty resolution in premium-level TV specification, but it is now the standard resolution for TV displays. As the next standard, UHD resolution is essential to servicing an enriched in-room experience. LG is leading the industry with a series of models suporting UHD resolution, delivering ultra-high customer satisfaction.

*note that available lineup may vary by region









IP Over Coax

IP Over Coax enables the service provider to provide interactive services to the guests over RF infrastructure. The DOCSIS* Ready Set top box may be used to upgrade conventional stand alone boxes to smart boxes. The upgrade not only enables smart functions but also opens a communication channel with customers over RF infrastructure, eventually generating greater service engagement. The upgrade offers a new channel to engage customers without revamping the existing RF infrastructure, making it highly cost-effective. The Pro: Centric Smart box is built with Wi-Fi connectivity, providing alternative option for guests to connect to wireless stream IP data without LAN cables.

- DOCSIS Ready STB
- Built-in WiFi

Customizable App

Interconnect the hotel system with the webOS Launcher bar. This customizable bar displays hotel services and facility information in an efficient and differentiated experience. Be distinguished from other hotels without the need to purchase solutions or install network infrastructure. Simple, and effective.



Smart IPTV

*Features may vary by each models and inches.

LG **COMMERCIAL TV** HIGHLIGHTS

*Features may vary by each models and inches.

COMMERCIAL TV

CATEGORY

LG

LG Commercial TVs are mainly classified into Pro:Centric® Smart, Pro:Centric® V, Commercial Lite and SuperSign TV.

Pro:Centric® SMART Web Smart Screen DIAL webRTC Share Share browser Pre-loaded Bluetooth WOL Diagnostics softAP Pro:Centric® Value External External Instant On Power Out TV Link MHL TV Signage (Commercial Lite) Welcome Remote **USB Auto** USB Clonine Hotel Mode Screen/ **Diagnostics** Playback+ (USB) Video Time External **IR OUT** RS-232C Multi IR Schedule Time

Scheduler

(First use)

TV Signage (Smart TV Signage)

SNMP

Enhanced Guest In-Room Entertainment

Enhanced OTT (Over The Top)

The LG commercial SMART TV raises the bar for in-room entertainment with OTT (Over The Top) content. It contains well-known, customer-preferred apps and delivers a more enjoyable customer experience. Apps can be preloaded and managed online by the recently upgraded Partner Portal*.

Download Smart Apps with LG Smart Hospitality Lounge



What's special?

Various Applications (Movie, Broadcast, Game, etc)

Download various Smart TV Applications dedicated to commercial environments such as hotels, airports.

Easy and Handy Management

Manage all applications of entire TVs with easy. You do not need to visit all rooms, what only you should do is to register your TVs on the site and download applications at once. You can manage applications by country and models.

Steps to Use Lounge

Step 1.	
Access to Partner	
Portal & Login	

Step 2.

Register Country and Smart TVs

Step 3. Download Apps

Step 4. Install Apps

Convenient Accessories

Even the TV's accessories make for a more comfortable hotel stay for guests. Not only can they enjoy vivid, high resolution images, but also the convenience of the external clock and swivel stand, for higher customer satisfaction and superior service quality.





External Clock

Swivel Commercial Stand

NTP Sync.

Timer

LG Pro:Centric®SMART with OLED

Pro:centric® Smart with OLED lineup provides LG's smartest hotel TV solution while overcoming the limits of current displays in both picture quality and design.



LG Pro:Centric®SMART with OLED

Why OLED Techonology

Perfect Black

Limitless contrast and the deepest blacks

Self-lighting pixels switch off completely to reproduce absolutes blacks with no light bleed, offering infinite contrast



Perfect Color

Accurate & stable color reproduction

Self-lighting pixels bring colors to life with superb accuracy.



Perfect Viewing Screen

Wide viewing angle

LG OLED Signage delivers awe-inspiring picture quality across the entire screen, even from wide viewing angles.



Perfect Design

Slim and light

LG's unbelievably lightweight and thin OLED display unlocks new worlds of design flexibility.









OLED Wallpaper Hotel TV

Picture-on-Wall Design

Slim as a blade

The thin, artistic design of the EV960H series blends perfectly into the wall without even the trace of a shadow.



Perfect Sound

4.2CH sound

LG OLED Wallpaper Hotel TV has separated 4.2ch. sound bar with moving speaker. By these LG's own special systems we can experience the sense of space of the scene.



Dolby Vision™ HDR

Active HDR

Dolby Vision™ is a technology that delivers intense highlights, vivid colors and deep black on the screen. LG OLED TV supports premium HDR contents mastered by Dolby Vision™ and is even compatible with generic HDR10.





SDR

HDR

EV960H EU



- OLED Wallpaper Hotel TV
- ULTRA HD
- Dolby Vision™ HDR, HDR10
- Picture-on-Wall Design
- Up-firing Speakers
- Solution : Pro:Centric® SMART / Direct / V
- SDK (GEM / Flash / HTML5)
- DRM : Pro:Idiom®
- Media Share
- Bluetooth Sound Sync, LG Sound Snyc
- Customizable App

55" / 65"

EW961H

• Blade Slim, CINEMA SCREEN

- OLED Surround
- DRM: Pro:Idiom®
- Media Share
- Bluetooth Sound Sync
- Solution: Pro:Centric® SMART / V / Direct
- HCAP (SDK): GEM / Flash / HTML5




EU / CIS

LG Pro:Centric®SMART


A PREMIUM SMART SOLUTION VIA IP & RF NETWORK

Pro:Centric® SMART is optimized for customizing hospitality services for hotel brands and guests through an IP & RF infrastructure. With its high picture quality, sophisticated design and advanced connectivity functions, it upscales in-room entertainment and increases convenience through implementation of high-end technology.



Pro:Centric® SMART Application Platform (IP)

LG Pro:Centric SMART offers extended customizable tools; HTML5, GEM and Flash. With these, the partners can optimize Commercial TVs to edit and develop their own enhanced service design. Also, it gives visual impact on and delivers messages to customers as users intend.



Pro:Centric® Server Application (RF)

You can now differentiate your hotel with our customizable templates and pages which can be specialized for your property. Pro:Centric® provides you a solution that is easily customizable for your business.



Annual Difference of the Park of the Community of the Com



Wake-up Setting

Weather Information

Various Features

PCA serves the convenience of the guest through a Wake-up setting, Weather Information, Map Service, and much more functions that you can choose.


Customizable Template & Page

Choose an alternative look & feel template based on your reference, and edit multiple sections with 40 pages of billboards by yourself with the web based tool.

Pro:Centric® Direct Support (IP)

Simply create your own templates and remotely manage TVs on the IP network with Pro:Centric Direct, LG's content management software. Pro:Centric Direct offers a free design template, along with customizable widgets and three types of theme templates (Cinematic-type, Grid-type, Bar-type) in order to promote branding and meet guests' tastes and needs. Its interactive solution, including 1-click service, and intuitive UI impress guests while elevating their hotel experience. Plus, for hoteliers, not only does it offer efficient content production and management, but it also maximizes advertisement effectiveness, which contributes to improving the hotel brand.







14 | 15

LG Pro:Centric®SMART

ULTRA HD TV

4K Resolution

ULTRA HD is the future of digital picture, possessing four times higher resolution than that of full HD. Stunning 8.3 million pixels gives a flawless picture quality and incredibly vivid detail.



4K Upscaler

Enjoy Full HD content in 4K ULTRA HD quality. The 4K Upscaler automatically upgrades Full HD content to ULTRA HD through the six steps of the upscaling processes.



Smart Connectivity

Smart Share

Smart Share allows users to share content more easily and quickly. It also searches for the content they want in order to share it more easily and accurately, there by simplifying the process of sharing between various devices.





Screen Share

Connect a smartphone or a laptop PC to TV via a Wi-Fi Direct connection. The TV will display the device's screen, and users can share their content and memories together.



Bluetooth Sound Sync

Bluetooth Sound Sync enables users to listen to music on a mobile device through TV speakers via Bluetooth connection.

* Support devices for Bluetooth Sound Sync : Android (above v4.4 KitKat) / iOS based Mobile Device



Smart Experience

webRTC Ready

webRTC provides an application development environment for video calling, video chat and P2P (Person-to-Person) file sharing. Guests can look at and communicate each other without visiting rooms.



* Separate server or SI's webRTC-based telecommunication solution is required for telecommunication between two TV sets.

SoftAP

SoftAP means Software enabled Access Point. This "Virtual" Wi-Fi feature executes by software working on the device to create a wireless hotspot.



* SoftAP should be set in installation menu after TV is on. * Smart Mirroring may not be operated at the same time.

Customizable App

Customizable app by web OS displays hotel information for guests. No need to purchase a server / solutions or install network infrastructure.



* Up to five customizable apps are available to be added and organized in the launcher bar.

Smart Management

Remote Diagnostics

Save big on the expenses of managing the commercial TVs with Remote Diagnostics. Real-time Remote Diagnostics report detects error in advance to prevent TVs from any malfunction.



Wake-up On LAN

WOL is the Ethernet computer networking standard to turn on TV or PC by transferring a network message. The message is transferred through another computer connected the same local ares.



Smart DRM

Pro:Idiom®

DRM(Digital Right Management) technology unlocks access to premium content to help assure rapid and broad deployment of HDTV and other high value digital contents.



65" / 55" / 49" / 43"

UV761H

55" / 49" / 43" / 32" / 28" / 24"

LV761H

EU / CIS



- ULTRA HD
- Dolby Vision™ HDR, HDR10
- Ultra Slim Design
- Commercial Swivel Stand (43", 49", 55")
- Solution : Pro:Centric® SMART / Direct / V
- SDK (GEM / Flash / HTML5)
- DRM: Pro:Idiom®
- Media Share
- · Bluetooth Sound Sync, LG Sound Snyc
- Customizable App
- Full HD (HD for 24" / 28") • Commercial Swivel Stand
- Solution: Pro:Centric®
- SMART / Direct / V • SDK (GEM / Flash / HTML5)
- DRM: Pro:Idiom®
- Media Share
- Bluetooth Sound Sync, LG Sound Snyc
- Customizable App

* 24"/28" is only for EU region.

55" / 49" / 43"

55" / 49" / 43" / 32" LX761H

EU UV661H

49" / 43" EU/CIS LV661H

EU



- Full HD
- Commercial Swivel Stand
- Solution : Pro:Centric® SMART / V
- SDK (GEM / Flash / HTML5)
- DRM : Pro:Idiom®
- Media Share
- Bluetooth Sound Sync



- ULTRA HD
- ·HDR10
- Commercial Swivel Stand
- Solution : Pro:Centric® SMART / Direct / V
- SDK (GEM / Flash / HTML5)
- DRM: Pro:Idiom®
- Media Share
- Bluetooth Sound Sync, LG Sound Snyc
- Customizable App




- Full HD
- Commercial Swivel Stand
- Solution : Pro:Centric® SMART / Direct / V
- SDK (GEM / Flash / HTML5)
- DRM: Pro:Idiom®
- Media Share
- Bluetooth Sound Sync, LG Sound Snyc
- Customizable App

LG Pro:Centric[®]v

COMPREHENSIVE HOSPITALITY SOLUTION VIA RF NETWORK

Pro:Centric® V provides comprehensive solutions in RF infrastructure. Through the Pro:Centric Server and Application, hoteliers are able to customize their settings in line with hotel branding concepts and deliver information on hotel facilities and wake-up call services, weather forecasts and other messages to guests, all while reinforcing the hotel's brand image.



Pro:Centric® Application Version 3.7 Upgraded Features

Pro:Centric Application v. 3.7 provides more intuitive and elegant templates than the previous version, and is available in 3 additional languages. This makes it easier for guests to access information and enables managers to deliver messages in a more effective way.

New Templates

Pro:Centric Application (PCA) v. 3.7 provides one new template, making a total of three templates, that customers can select according to their preference.



Welcome Image of PCA v3.7

39 Languages

39 languages including Hebrew, Arabic and Farsi, and language alignment are supported, making your guests' stay a more comfortable one.



Right Alignment (Hebrew, Arabic, Farsi)



Left Alignment (36 languages)

Easy Content Creation & Management

Customizable Template & Page

Choose an alternative look & feel template based on your preference, and edit multiple sections with 40 pages of billboards by yourself with the web based tool. (Max 15pages / section Available)



*Based on PCA 3.7

Multi Channel Spooling

Operation of up to 8 hotel channels (22 sub-channels) can offer various information and added services.



PMS Interfaced Services

The Pro:Centric® Application offers guest-centric services, such as a welcome page with the guest's name, auto language setting and billing information with the Property Management System (PMS) interface.

Welcome Message

Warm greeting message including guest's name.



Automatic Language Setting

Default language settings based on the guest's nationality.



Billing Info

Guest's billing information automatically updated via PMS.



LG Pro:Centric[®]v

Features

EzManger

EzManager provides convenient installation function that helps to set up Pro:Centric TV settings automatically without extra effort of configuration. Auto-installation requires 1~3 minutes while manual installation requires 3~5 minutes.



Instant On

The high speed loading system enables users to enjoy content immediately after turning on the TV.



External Power Out

No extra set-top box power cable is necessary for STB usage. Just connect your STB to LG Hotel TV without a need for extra power but be supplied all from LG Hotel TV.




Welcome Video/screen

Easily attach an external clock to your hospitality TV. Guests can quickly check the time just by looking at the TV, and all it needs is an RGB interface connection.



One Channel Map

The One Channel Map feature allows users to edit and list the channels of their choosing from any of the various broadcasting signals.



Commercial Swivel Stand

Expand the rage of comfort for the guests with a commercial grade stand by allowing them to watch a TV from any angle.



Hotel Quick Menu

You can now enjoy LG's simple home menu solution, Hotel Quick Menu. It provides editable welcome message, date/time and other frequently used menus in the form of bar. These can be all set with a remote control or USB, and guests are able to easily access the menus they want improving satisfaction of their stay.



55" / 49" / 43" / 32"

LV541H

- Full HD
- Commercial Swivel Stand
- Solution : Pro:Centric® V / Hotel Quick Menu
- EzManager for quick and simple TV settings
- Embedded Customizable Templates*
- PMS Interfaced Service Ready
- TV Link Interactive
- Instant On, External Power, External Clock Ready
- Hotel Quick Menu
- $\ensuremath{^{\star}}$ It is available when the TV is connected to Pro:Centric server.

55" / 49" / 43" / 32"

LV341H





• Solution : Pro:Centric® V / Hotel Quick Menu

• EzManager for quick and simple TV settings

• Embedded Customizable Templates*

PMS Interfaced Service Ready

Hotel Quick Menu

* It is available when the TV is connected to Pro:Centric server.

"/49"/43"/32" J**ЭЛ**4II



EU

EU/CIS

TV Signage (Commercial Lite)

ESSENTIAL COMMERCIAL TVS TAILORED TO COMMERCIAL ENVIRONMENTS

Improve management efficiency and offer a warmer welcome to guests. Featuring Welcome Video/ Image, USB Cloning and other convenient functions, LG Commercial Lite TVs are able to lighten the management burden and make customers feel cared for in numerous business environments.



Features

USB Auto Playback+

Create and sequentially play playlists composed of informative media (video, music and image) you choose without PC and any installation.



Time scheduler

Create your own time scheduler of your Commercial TV. Once you set opening/ closing hours and holidays, the TV will turn on/off according to work schedule.



USB Cloning

Clone all commercial TVs with stonishing speed and ease. The USB Cloning feature allows you to simply copy the TV settings to all TVs using a USB memory device.



Firmware Update TV Setting Cloning

Welcome Video/screen

With the capability to display repeatedly various video formats as well as images, Commercial Lite TVs allow for a greater variation of greeting messages in hotel rooms which make customers feel more welcome and cared for.



Hotel Mode

Be in total control with Hotel Mode. Have the capability to change every TV setting, or reset to default in every room.



Multi IR

Multi IR function eliminates the remote control signal interference between TVs in multiple dwelling beds. This system will work using the same LG TV model.



TV Signage (Commercial Lite)

Features

External Speaker Out

Enhance the entertainment experience by adding an additional speaker. Guests listen to and control the TV audio from anywhere in the business areas, including restrooms.




IR Out

Using the interactive set-top-box, all LG TVs can be controlled with a single remote.



Via the TV's RS-232C port, you can remotely control power and volume settings simultaneously.







75" / 65"

UV341C EU / CIS



- ULTRA HD
- webOS 3.0
- Media Share
- Bluetooth Sound Sync, LG Sound Snyc
- Pre-loaded YouTube App, Web Browser
- Crestron Connected® Certified
- DPM (Display Power Management) Mode
- WOL (Wake On LAN), SNMP
- Youtube App

55" / 49" / 43" / 32"

LV340C

EU / CIS



- Crestron Connected® Certified
- WOL (Wake On LAN), SNMP
- Diagnostics (USB)
- Welcome Video / Screen
- IR Out, USB Cloning, External Speaker Out
- USB Auto Playback+, Time Scheduler

28" / 24"

LW341C





- Diagnostics (USB)
- Welcome Video/Screen
- IR Out, USB Cloning, External SPK Out
- USB Auto Playback+, Time Scheduler
- Built In Power

49" / 43" / 32"

LV300C

EU



- Full HD (32": HD)
- Diagnostics (USB)
- Welcome Video/Screen
- IR Out, USB Cloning
- USB Auto Playback+, Time Scheduler

EU

TV Signage (Smart TV Signage)

LIVE TV AND ADVERTISEMENTS ON ONE SCREEN

SuperSign TV enables both TV broadcasting and promotional display in one screen via a built-in TV tuner. With SuperSign TV, managers can efficiently and timely deliver messages / promotion while customers enjoy watching live TV simultaneously. SuperSign TV will help you to achieve ease of efficient operation.



55" / 49" / 43"

LV640S



- $\bullet\,\mathsf{Full}\,\mathsf{HD}$
- Built-in Speaker and TV Tuner
- TV Embedded CMS (Content Management Software)
- $\bullet \, \mathsf{Simpe} \, \mathsf{Editor} \, / \, \mathsf{SuperSign^{\mathsf{TM}}} \, \mathsf{Link} \, / \, \mathsf{SuperSign^{\mathsf{TM}}} \, \mathsf{W} \, \mathsf{Compatibility}$


EU / CIS

- Media Share via Built-in WiFi
- Pre-loaded YouTube App, Web Browser
- Crestron Connected® Certified
- RTC (Real Time Clock), NTP (Network Time Protocol)
- WOL (Wake On LAN), SNMP

Features

Simple Connectivity

With Wi-Fi dongle support, distribution of advertisement content has been simplified. By removing the need of an external media player and Ethernet/RS-232C cables, the total cost of ownership (TCO) can be reduced.



Fail Over (Internal Memory only)

The USB fail over function enables content to be displayed without dead spots when no input signal is available. This feature supports files in JPG format with a maximum file size of 10 MB.




RTC

Save time and improve convenience with RTC (Real Time Clock). When the TV's power is off, time information is stored on the RTC module via an internal memory, and a time sync process can be omitted as the TV turns on.




NTP

With NTP (Network Time Protocol), the TV receives real time updates from the network and synchronizes its time accordingly.



SuperSign™ Solutions

The SuperSign™ Solution includes SuperSign Control, Simple Editor to provide digital media editing, scheduling, distribution and management capabilities.



Peripherals

Set Top Box

Modular type Set Top Box with WebOS

STB-5500



- Pro:Centric® SMART IPTV Platform
- IP Streaming and RF Tuning
- ULTRA HD Channel Support
- Pro:Centric® Application Support for non-Pro:Centric TVs
- External Module Expansion Ready
- (DOCSIS 3.0 Modem Option Available*) SmartShare, ScreenShare (Miracast)
- Embedded Pro:Idiom® decryption
- * DOCSIS 3.0 modem can be available / expanded through a third party system integrator.

Pro:Centric Server

Simple Content Management via RF or IP Distribution Network

PCS400R



- Support IP/ RF Infrastructure
- Fully Customizable Content with Intuitive Template Atom quad core 1.9GHz (2.56GHz burst)
- Remote and Channel Management
- Interactive Service and Advertisement
- Support SSD (Solid-State Drive)
- •8GBRAM
- Commercial off-the-shelf Linux OS
- * Please check product release date and compatible models with regional sales persons.

Accessories

Several Accessories Ready for Commercial TVs

LEC-005

External Clock

Hotel Simple RCU

Simple Remote



- Automatic Time Setting (Summer Time)
- Attaching Method with 3M Dual Stickers (Black)
- Alarm/Buzzer/Luminance Control Available
- TV Side Housing: RJ12 Connector (LEC-005), RGB Connector (LEC-003)



- Simple Remote Controller with 19 keys
- Infrared
- Multi IR Code (1/9)
- Color: Black

AN-MR650/600

Magic Remote

LTC* Simple RCU

Simple Remote



- Gesture, Pointing, Wheel Control
- Number Key Pad
- Magic Zoom



- Simple Remote Controller with 7 keys
- Infrared
- · Antibacterial Surface to be cleaned with water and alcohol
- Multi IR Code (1/4) Color: White

*LTC (Long Term Care)

EU / CIS Line up

UV761H: 65"

UV761H: 65" / 55" / 49" / 43" **UV661H:** 55" / 49" / 43"

LV761H: 55" / 49" / 43" / 32" / 28" / 24"

LV661H: 49" / 43" **LX761H:** 55" / 49" / 43"

EW961H: 65" / 55"

LV541H: 55" / 49" / 43" / 32" **LV341H**: 55" / 49" / 43" / 32"

UV341C: 76" / 65"

EU

EV960H: 65"

CIS


EW961H: 65" / 55"

UV661H: 55" / 49" / 43" LV761H: 55" / 49" / 43" / 32"

LV541H: 55" / 49" / 43" / 32"

UV341C: 75" / 65" LV340C: 55" / 49" / 43" / 32" **LV300C**: 49" / 43" / 32"

LV640S: 55" / 49" / 43"



Pro:Centric® SMART with OLED

100 ~ 240V, 50 / 60Hz

55" : 253.1 65" : 283.5

		EVOCOL	EU/CIS
	_	EV960H	EW961H
Size		65"	55" / 65"
Panel	Resolution	3,840 x 2,160 (4K UHD)	3,840 x 2,160 (4K UHD)
Broadcasting System	110001111111	DVB-T2 / C / S2	DVB-T2 / C / S2
HDR		HDR 10 / HDR Dolby Vision	HDR 10 / HDR Dolby Vision
Audio Output			-
Speaker System		30W + 30W / 4.2 CH	20W + 20W / 4.0CH
Hospitality Solution	Pro:Centric® Type Quick Menu	• (Smart, V, Direct)	• (Smart, V, Direct)
iospitality solution	DRM	Pro:ldiom	- Pro:Idiom
	webOS	• (webOS 3.5)	• (webOS 3.0)
		(WEDOS 3.3)	(webos 3.0)
	Web Browser		
mart Feature	Pre-loaded App	•	•
mart Feature	Soft AP	•	•
	Screen Share	• (G + G -)	(5 + 5 + 2 + 2 + 2 + 2 + 2 + 2 + 2 + 2 +
	Smart Share	• (Smart Share)	• (Smart Share)
	Bluetooth Sound Sync / LG Sound Sync	• / •	• / •
asy Installation	EzManager (Simplicity)	•	•
,	USB Cloning	•	•
	Wake on RF	•	•
	WOL (Wake On LAN)	•	•
	SNMP	•	•
	Diagnostics	• (Remote Diagnostics)	• (Remote Diagnostics)
lanagement	TVLink Interactive	•	•
	HTNG/HDMI-CEC	(1.4) / • (1.4)	(1.4) / • (1.4)
	IR Out	• (RS-232C, HDMI)	• (RS-232C, HDMI)
	Multi IR Code	(113 2320,115111)	(13 2320,1151011)
	Welcome Screen / Video	• / -	• / -
	One Channel Map	•	•
		•	•
	External Speaker Out	•	•
ospitality Features	Instant ON		
	External Power	•	•
	External Clock Compatibility	-	<u> </u>
	USB Auto playback / USB Auto playback+	-	- <u>-</u>
	Anti-theft Dongle Cover	-	
	Crestron Certified Compatibility	-	
	Time Scheduler / First Use	-	
ignage Features	RTC (Real Time Clock)	-	-
	NTP Sync Timer	-	-
	SuperSign SW Compatibitlity		
	Headphone Out	-	
	HDMI In	-	1 (2.0, 6G)
iterface (Set Side)	USB	_	3 (3.0 x 1, 2.0 x 2)
	CI Slot	_	1
	RF In	2	2
Interface (Set Rear)	AV In	1 (Phone Jack Type)	1 (Phone Jack Type)
	Full Scart	i (Filone Jack Type)	(Filone Jack Type)
	Component In (Y, Pb, Pr-Video)	1 (Dhana Indi Tima)	1 (Dhone Ingly Type)
		1 (Phone Jack Type)	1 (Phone Jack Type)
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	1 (Optical)
	HDMI / HDCP Input	2 (2.0)	1 (2.0, 6G)
	USB	2 (3.0, 2.0)	
	RGB In (D-sub 15pin) - PC	-	-
	PC Audio Input	-	-
	RS-232C (D-Sub 9pin)	1 (Control & Service)	1
	Headphone Out	-	1
	Clock Interface (D-sub 15pin)		
	RJ45 (Usage Purpose)	2 (Ethernet, Aux)	2
	External Speaker Out (3.5mm Phone Jack)	2 (Spk-out 1, Vol. Control 1)	2 (Spk-out 1, Vol. Control 1)
	TV link Configuration (Phone Jack Type)	-	
	Debug (Phone Jack Type)	_	
	Anti-theft System	Kensington Lock (AIO BOX)	 Kensington Lock
	•		
imension	W x H x D / Weight (with stand) Unit : mm / kg	1,450 x 825 x 3.85 / 7.6	55" : 1,229 x 759 x 225 / 18.6 65" : 1,451 x 882 x 225 / 25.4

100 ~ 240V, 50 / 60Hz

65":471

Voltage, Hz

Typical (Watts)

Power

LG Commercial TV

		Ed Commercial 1	
		Pro:Centri	c® SMART
		EU	EU / CIS
		UV761H	UV661H
Size		43" / 49" / 55" / 65"	43" / 49" / 55"
Panel	Resolution	3,840 x 2,160 (4K UHD)	3,840 x 2,160 (4K UHD)
Broadcasting System		DVB-T2 / C / S2	DVB-T2 / C / S2
HDR		HDR 10 / HDR Dolby Vision	HDR 10
Audio Output		10/4/ . 10/4// 20 CH	1014/ . 1014//2011
Speaker System		10W + 10W / 2.0 CH	10W + 10W / 2.0 CH
	Pro:Centric® Type	• (Smart, V, Direct)	• (Smart, V, Direct)
lospitality Solution	Quick Menu	-	
	DRM	Pro:ldiom	Pro:ldiom
	webOS	• (webOS 3.5)	• (webOS 3.5)
	Web Browser	•	•
	Pre-loaded App	•	•
mart Feature	Soft AP	•	•
	Screen Share Smart Share	• (Smart Share)	• (Smart Share)
		(Smart Snare) • / •	• (Smart Snare)
	Bluetooth Sound Sync / LG Sound Sync		
asy Installation	EzManager (Simplicity) USB Cloning	•	•
	Wake on RF	•	•
	WOL (Wake On LAN)	•	•
	SNMP	•	•
	Diagnostics	• (Remote Diagnostics)	• (Remote Diagnostics)
/lanagement	TVLink Interactive	•	•
	HTNG/HDMI-CEC	• (1.4) / • (1.4)	• (1.4) / • (1.4)
	IR Out	• (RS-232C, HDMI)	• (RS-232C, HDMI)
	Multi IR Code	•	•
	Welcome Screen / Video	• / -	• / -
	One Channel Map	•	•
	External Speaker Out	•	•
lospitality Features	Instant ON	•	•
iospicality i catalitis	External Power	•	•
	External Clock Compatibility	• (LEC-005)	• (LEC-005)
	USB Auto playback / USB Auto playback+		
	Anti-theft Dongle Cover	•	•
	Crestron Certified Compatibility Time Scheduler / First Use	-	
ignage Features	RTC (Real Time Clock)	-	-
igriage reacures	NTP Sync Timer	-	
	SuperSign SW Compatibitlity		
	Headphone Out		
	HDMI In	1 (2.0)	1 (2.0)
nterface (Set Side)	USB	2 (1EA 3.0, 1EA 2.0)	2 (1EA 3.0, 1EA 2.0)
	CI Slot	1	1
	RF In	2	2
	AV In	1 (Phone Jack Type)	1 (Phone Jack Type)
Interface (Set Rear)	Full Scart	-	-
	Component In (Y, Pb, Pr-Video)	1 (Phone Jack Type)	1 (Phone Jack Type)
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	1 (Optical)
	HDMI / HDCP Input	1 (2.0)	1 (2.0)
	USB		
	RGB In (D-sub 15pin) - PC	-	
	PC Audio Input		- 1/0 - 100 - 1
	RS-232C (D-Sub 9pin)	1 (Control & Service)	1 (Control & Service)
	Headphone Out	1 (012)	1 (0112)
	Clock Interface (D-sub 15pin) RJ45 (Usage Purpose)	1 (RJ12) 2 (Ethernet, Aux)	1 (RJ12) 2 (Ethernet, Aux)
	External Speaker Out (3.5mm Phone Jack)	2 (Etnernet, Aux) 2 (Spk-out 1, Vol. Control 1)	2 (Etnernet, Aux) 2 (Spk-out 1, Vol. Control 1)
	TV link Configuration (Phone Jack Type)		
	Debug (Phone Jack Type)		
	Anti-theft System	Kensington Lock, Credenza Hole, Lock Down Plate	Kensington Lock, Credenza Hole, Lock Down Plat
	a.c. c jocciii	43" : 967.6 x 617.2 x 303 / 13.4	
Dimension	W x H x D / Weight (with stand) Unit : mm / kg	49":1,100.1 x 695.8 x 303 / 15.9 55":1,236 x 770.7 x 303 / 18.5 65":1,455.2 x 898.1 x 312.4 / 25.5	43" : 977 x 630 x 303 / 11.2 49" : 1,110 x 705 x 303 / 14.5 55" : 1,249 x 783 x 303 / 17.4
	Voltage, Hz	100 ~ 240V, 50 / 60Hz	100 ~ 240V, 50 / 60Hz
	- 5.tage, 112	43":114.2	
Power	Typical (Matts)	49" : 130.9	43" : 91.0 49" : 110.7
	Typical (Watts)	55" : 132	49 : 110.7 55" : 142.6
		65" : 170	JJ . 142.U

		Pro:Centric® SMART	
		EU/CIS LV761H	EU/CIS LV761H
Size		32" / 43" / 49" / 55"	24H" / 28H"
Panel	Resolution	1,920 x 1,080 (FHD)	1,366 x 768 (HD)
Broadcasting System		DVB-T2 / C / S2	DVB-T2 / C / S2
HDR		- 1014/ 1014/ 20 611	
Audio Output / Speaker System		10W + 10W / 2.0 CH (32" : 5W + 5W / 2.0CH)	5W + 5W / 2.0CH
/ Speaker System	Pro:Centric® Type	• (Smart, V, Direct)	• (Smart, V, Direct)
Hospitality Solution	Quick Menu	- (Smar, v, brice)	- (Smarc, v, Birece)
, ,	DRM	Pro:ldiom	Pro:ldiom
	webOS	• (webOS 3.5)	• (webOS 3.5)
	Web Browser	•	•
Consut Footure	Pre-loaded App Soft AP	•	•
Smart Feature	Screen Share	•	•
	Smart Share	• (Smart Share)	• (Smart Share)
	Bluetooth Sound Sync / LG Sound Sync	• / •	• / •
Facy Installation	EzManager (Simplicity)	•	•
Easy Installation	USB Cloning	•	•
	Wake on RF	•	•
	WOL (Wake On LAN) SNMP	•	•
	Diagnostics	• (Remote Diagnostics)	• (Remote Diagnostics)
Management	TVLink Interactive	• (Nerriote Biagnostics)	• (Nemote Biagnostics)
	HTNG/HDMI-CEC	• (1.4) / • (1.4)	• (1.4) / • (1.4)
	IR Out	• (RS-232C, HDMI)	• (RS-232C, HDMI)
	Multi IR Code	•	•
	Welcome Screen / Video	• / -	• / -
	One Channel Map External Speaker Out	•	•
	Instant ON	•	•
Hospitality Features	External Power	•	•
	External Clock Compatibility	• (LEC-005)	-
	USB Auto playback / USB Auto playback+	-	-
	Anti-theft Dongle Cover	• (except 32")	-
	Crestron Certified Compatibility Time Scheduler / First Use	-	-
Signage Features	RTC (Real Time Clock)	•	
	NTP Sync Timer	-	-
	SuperSign SW Compatibitlity		
	Headphone Out	-	1
Interface (Set Side)	HDMI In	1 (1.4)	1 (1.4)
` ,	USB	2 (2.0)	1 (2.0)
	CI Slot RF In	1 2	2
	AV In	1 (Share with Component)	1 (Share with Component)
	Full Scart	-	-
	Component In (Y, Pb, Pr-Video)	1 (Phone Jack Type)	1 (Phone Jack Type)
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	1 (Optical)
	HDMI / HDCP Input USB	1 (1.4)	1 (1.4)
	RGB In (D-sub 15pin) - PC	-	1 (2.0)
Interface (Set Rear)	PC Audio Input	-	
	RS-232C (D-Sub 9pin)	1 (Control & Service)	1 (Control & Service)
	Headphone Out	1	-
	Clock Interface (D-sub 15pin)	1 (RJ12)	-
	RJ45 (Usage Purpose) External Speaker Out (3.5mm Phone Jack)	2 (Ethernet, Aux) 2 (Spk-out 1, Vol. Control 1)	1 (Ethernet) 2 (Spk-out 1, Vol. Control 1)
	TV link Configuration (Phone Jack Type)	2 (3px-out 1, voi. Control 1)	- (σρκ-σαι 1, νοι COΠΙΙΟΙ 1)
	Debug (Phone Jack Type)	-	
	Anti-theft System	Kensington Lock, Credenza Hole, Lock Down Plate	Kensington Lock, Credenza Hole, Lock Down Plate
Dimension	W x H x D / Weight (with stand) Unit : mm / kg	32" : 739 x 495 x 241 / 61 43" : 974 x 625 x 303 / 12.5 49" : 1,107 x 702 x 303 / 14.6 55" : 1,241 x 770 x 303 / 19.7	24":556 x 384.3 x 140.6 / 3.7 28":641.5 x 430 x 175 / 4.9
	Voltage, Hz	100 ~ 240V, 50 / 60Hz	100 ~ 240V, 50 / 60Hz
Power	Typical (Watts)	32" : 48 43" : 73.8 49" : 83 55" : 105	24":33.0 28":38.2

LG Commercial TV

Pro-Centric* SMART	
A3" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 32" / 43" / 49" 55"	
Size	
Panel Resolution 1,920 x 1,080 (FHD) DVB-T2 / C / S2	
DVB-T2/C/S2 DVB-T2/C/S2 DVB-T2/C/S2	
### Audio Output 10W + 10W / 20 CH 10W + 10W / 20 CH	
Number N	
Speaker System	
DRM	
Web Browser	
Web Browser	
Pre-loaded App	
Soft AP	
Screen Share	
Smart Share	
Bluetooth Sound Sync / LG Sound Sync -/ * -/ *	
Ezwanager (Simplicity)	
Section Sect	
Wake on RF	
Management Man	
SNMP	
TVLink Interactive	
TVLink Interactive	
IR Out	
Multi IR Code	
Welcome Screen / Video • / - • / -	
One Channel Map	
External Speaker Out	
Instant ON	
External Power - - - -	
External Power - (LEC-003)	
USB Auto playback / USB Auto playback +	
Anti-theft Dongle Cover ●	
Crestron Certified Compatibility - - -	
Time Scheduler / First Use	
RTC (Real Time Clock) - - - NTP Sync Timer - - SuperSign SW Compatibitlity - Headphone Out - 1 HDMI In 1 (1.4) 1 (2.0) USB 2 (2.0) 2 (2.0) CI Slot 1 1 1 RF In 2 2 2 AV In 1 (Share with Component) - Full Scart - 1 Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) + (1.4) 1 (2.0)	
NTP Sync Timer - -	
SuperSign SW Compatibitlity	
Headphone Out	
HDMI In	
USB 2 (2.0) 2 (2.0) CI Slot 1 1 RF In 2 2 AV In 1 (Share with Component) - Full Scart - 1 Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
CI Slot	
RF In 2 2 AV In 1 (Share with Component) - Full Scart - 1 Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
AV In 1 (Share with Component) - Full Scart - 1 Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
Full Scart - 1 Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
Component In (Y, Pb, Pr-Video) 1 (Phone Jack Type) - Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
Digital Audio Out (Coaxial / Optical) - 1 (Optical) HDMI / HDCP Input 1 (1.4) 1 (2.0)	
HDMI / HDCP Input 1 (1.4) 1 (2.0)	
USB	
RGB In (D-sub 15pin) - PC	
nterface (Set Rear) PC Audio Input	
RS-232C (D-Sub 9pin) 1 (Control & Service) 1	
Headphone Out	
Clock Interface (D-sub 15pin)	
RJ45 (Usage Purpose) 1 (Ethernet) 2	
External Speaker Out (3.5mm Phone Jack) 2 (Spk-out 1, Vol. Control 1) 2 (Spk-out 1, Vol. Control 1))
TV link Configuration (Phone Jack Type)	
Debug (Phone Jack Type)	
Anti-theft System Kensington Lock, Credenza Hole, Lock Down Plate Kensington Lock, Credenza Hole, Lock Do	wn Plat
32" : 734 × 489 × 282 / 8.2	2
Dimension Wx Hx D / Weight (with stand) 43":977 x 630 x 303 / 11.2 43":973 x 624 x 325 / 13.	
Unit:mm/kg 49:1,110 x /05 x 303 / 14.5 49:1,106 x /01 x 325 / 17	
55":1,242 x 780 x 325 / 21 Voltage, Hz 100 ~ 240V, 50 / 60Hz 100 ~ 240V, 50 / 60Hz	.1
Voltage, Hz 100 ~ 240V, 50 / 60Hz 100 ~ 240V, 50 / 60Hz 32":62.8	
Power 13" - 662 13" - 84.2	
1ypical (watts) 49" :88.7 49" :85.2	
55" :100.1	

		Pro:Centric® V	
		EU / CIS	EU
		LV541H	LV341H
Size		32" / 43" / 49" / 55"	32" / 43" / 49" / 55"
Panel	Resolution	1,920 x 1,080 (FHD)	1,920 x 1,080 (FHD)
Broadcasting System	Resolution	DVB-T2 / C / S2	DVB-T2 / C / S2
HDR		-	-
Audio Output / Speaker System		10W + 10W / 2.0 CH (32" : 5W + 5W / 2.0 CH)	10W + 10W / 2.0 CH (32" : 5W + 5W / 2.0 CH)
	Pro:Centric® Type	• (V)	• (V)
Hospitality Solution	Quick Menu	•	•
	DRM	<u> </u>	-
	webOS Web Browser		<u>-</u>
	Pre-loaded App		-
Smart Feature	Soft AP		-
	Screen Share		_
	Smart Share	-	-
	Bluetooth Sound Sync / LG Sound Sync	-	-
Easy Installation	EzManager (Simplicity)	•	•
	USB Cloning		•
	Wake on RF	•	•
	WOL (Wake On LAN)	<u>-</u>	-
	SNMP Diagnostics	• (Self Diagnostics(USB))	• (Self Diagnostics(USB))
Management	TVLink Interactive	(Sett Diagnostics(OSD))	- (Self Diagnostics(OSD))
	HTNG/HDMI-CEC	• (1.4) / • (1.3)	• (1.4) / • (1.3)
	IR Out	• (RS-232C, HDMI)	• (RS-232C)
	Multi IR Code	•	•
	Welcome Screen / Video	• / •	• / •
	One Channel Map	•	•
	External Speaker Out	•	•
Hospitality Features	Instant ON	•	-
	External Power External Clock Compatibility	• (LEC-005)	-
	USB Auto playback / USB Auto playback+	• (LEC-003)	• / -
	Anti-theft Dongle Cover	• (except 32")	• (except 32")
	Crestron Certified Compatibility	-	-
	Time Scheduler / First Use	• / -	• / -
Signage Features	RTC (Real Time Clock)		-
	NTP Sync Timer		-
	SuperSign SW Compatibitlity		1
	Headphone Out HDMI In	2 (1.4)	1 (1.4)
Interface (Set Side)	USB	1 (2.0)	1 (2.0)
	CI Slot	1	1
	RF In	2	2
Interface (Set Rear)	AV In	1 (Share with Component)	1 (Share with Component)
	Full Scart	-	-
	Component In (Y, Pb, Pr-Video)	1 (RCA5 Type)	1 (RCA5 Type)
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	1 (Optical)
	HDMI / HDCP Input USB	1 (1.4)	1 (1.4)
	RGB In (D-sub 15pin) - PC		
	PC Audio Input		1 (Share with Component Audio)
	RS-232C (D-Sub 9pin)	1 (Control & Service)	1 (Control & Service)
	Headphone Out	1	-
	Clock Interface (D-sub 15pin)	1 (RJ12)	-
	RJ45 (Usage Purpose)	1 (SNMP)	1 (SNMP)
	External Speaker Out (3.5mm Phone Jack)	2 (Spk-out 1, Vol. Control 1)	1 (Spk-out 1)
	TV link Configuration (Phone Jack Type)		-
	Debug (Phone Jack Type) Anti-theft System	Kensington Lock, Credenza Hole, Lock Down Plate	- Kensington Lock Credenza Hole Lock Down Dlate
	And their System	32" : 739 x 495 x 241 / 6.1	32" : 739 × 495 × 241 / 6.1
Dimension	W x H x D / Weight (with stand) Unit : mm / kg	43" : 974 x 625 x 303 / 12.5 49" : 1,107 x 702 x 303 / 14.6	43" : 974 x 625 x 303 / 12.5 49" : 1,107 x 702 x 303 / 14.6
	Valtage III	55":1,241 x 770 x 303 / 19.7	55" : 1,241 x 770 x 303 / 19.7
	Voltage, Hz	100 ~ 240V, 50 / 60Hz 32" : 40.7	100 ~ 240V, 50 / 60Hz 32" : 40.7
Power	Timical (Matta)	43" : 62.7	43" : 62.7
	Typical (Watts)	49" : 74.2	49" : 74.2
		55" :95.2	55" : 95.2

LG Commercial TV

		Commercial Lite	
		EU/CIS UV341C	EU/CIS LV340C
Size		65" / 75"	32" / 43" / 49" / 55"
Panel	Resolution	3,840 x 2,160 (4K UHD)	1,920 x 1,080 (FHD)
Broadcasting System		DVB-T2 / C / S2	DVB-T2 / C / S2
HDR Audio Output / Speaker System		- 10W + 10W / 2.0 CH	- 10W + 10W / 2.0 CH (32" : 5W + 5W / 2.0 CH)
,	Pro:Centric® Type		-
Hospitality Solution	Quick Menu		-
1 7	DRM	_	-
	webOS	• (webOS 3.0)	-
	Web Browser	•	-
	Pre-loaded App	• (Youtube Only)	-
Smart Feature	Soft AP	•	-
	Screen Share	•	_
	Smart Share	• (Smart Share)	-
	Bluetooth Sound Sync / LG Sound Sync	• / •	-
	EzManager (Simplicity)	-	-
Easy Installation	USB Cloning	•	•
	Wake on RF		
	WOL (Wake On LAN)	(Magic packet only)	•
	SNMP	(Iviagic packet UTIIy)	•
		• (Self Diagnostics(USB))	
Management	Diagnostics T/Link Interactive		• (Self Diagnostics(USB))
	TVLink Interactive	TVLink Tuner	- (1 1) (- (1 2)
	HTNG/HDMI-CEC	• (1.4) / • (1.4)	• (1.4) / • (1.3)
	IR Out	• (RS-232C , HDMI)	• (RS-232C)
	Multi IR Code	•	•
	Welcome Screen / Video	• / -	• / •
	One Channel Map	•	•
	External Speaker Out		•
Hospitality Features	Instant ON		-
riospicality reactives	External Power		-
	External Clock Compatibility		-
	USB Auto playback / USB Auto playback+	• / -	• / •
	Anti-theft Dongle Cover	-	-
	Crestron Certified Compatibility	•	•
	Time Scheduler / First Use	-	• / -
Signage Features	RTC (Real Time Clock)		-
5 5	NTP Sync Timer	_	-
	SuperSign SW Compatibitlity		
	Headphone Out		1
	HDMI In	2 (2.0)	1 (1.4)
Interface (Set Side)	USB	1 (2.0)	1 (2.0)
	CI Slot	1	1
	RF In	2	2
	AV In		1 (Share with Component)
Interface (Set Rear)	Full Scart		- (Share with component)
	Component In (Y, Pb, Pr-Video)		1 (RCA5 Type)
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	1 (Optical)
	HDMI / HDCP Input	1 (2.0)	1 (1.4)
	USB	- (2.0)	- (1.4)
	RGB In (D-sub 15pin) - PC		
		-	1 (Share with Component Audio)
	PC Audio Input RS-232C (D-Sub 9pin)	1 (Phone Jack Type, Control & Service)	1 (Control & Service)
	Headphone Out	1 (Phone Jack Type, Control & Service)	i (Control & Service)
	Clock Interface (D-sub 15pin)	1 (Ethornot)	- 1 (CNIMD)
	RJ45 (Usage Purpose)	1 (Ethernet)	1 (SNMP)
	External Speaker Out (3.5mm Phone Jack)	<u>-</u>	1 (Spk-out 1)
	TV link Configuration (Phone Jack Type)	-	-
	Debug (Phone Jack Type)		-
	Anti-theft System	Kensington Lock	Kensington Lock
Dimension	W x H x D / Weight (with stand) Unit : mm / kg	65" : 1,456 × 902 × 335.9 / 27.6 75" : 1,697 × 1,038 × 367.5 / 44.3	32":739 x 472 x 168 / 4.9 43":974 x 625 x 220 / 9.3 49":1,107 x 701 x 235 / 11.4
	V Is II	100 2407 50 750 1	55" : 1,241 x 775 x 216 / 16.6
	Voltage, Hz	100 ~ 240V, 50 / 60Hz	100 ~ 240V, 50 / 60Hz
Power	Typical (Watts)	65" : 135.2 75" : 189.9	32" : 37.7 43" : 62.7 49" : 74.2 55" : 95.2

LG Commercial TV

Smart TV Signage

EU / CIS

LV640S

		LV6405	
Size		43" / 49" / 55"	
	Desclution		
Panel	Resolution	1,920 x 1,080 (FHD)	
Broadcasting System		DVB-T2 / C / S2	
HDR		-	
Audio Output		10W + 10W / 2.0 CH	
/ Speaker System		1000 1 1000 / 2.0 CH	
	Pro:Centric® Type	-	
Hospitality Solution	Quick Menu	-	
	DRM	-	
	webOS	• (webOS 3.5)	
	Web Browser	•	
	Pre-loaded App	• (Youtube Only)	
Smart Feature	Soft AP	• (Toutable Officy)	
Siliai t i eature	Screen Share	•	
	Smart Share	Smart Share (Photo&Video)	
		, ,	
	Bluetooth Sound Sync / LG Sound Sync	• / -	
Easy Installation	EzManager (Simplicity)	-	
	USB Cloning	•	
	Wake on RF	-	
	WOL (Wake On LAN)	•	
	SNMP	•	
	Diagnostics	• (Self Diagnostics(USB))	
Management	TVLink Interactive	TVLink Tuner	
	HTNG/HDMI-CEC	-/ • (1.4)	
	IR Out	• (RS-232C)	
	Multi IR Code	(K5-232C)	
	Welcome Screen / Video	-/•	
	One Channel Map	•	
	External Speaker Out	•	
Hospitality Features	Instant ON	-	
nospitality reactives	External Power	-	
	External Clock Compatibility	-	
	USB Auto playback / USB Auto playback+	-	
	Anti-theft Dongle Cover	-	
	Crestron Certified Compatibility	•	
	Time Scheduler / First Use		
Signage Features	RTC (Real Time Clock)	•	
Signage reacures		·	
	NTP Sync Timer	C C' L' C' L E L' AM	
	SuperSign SW Compatibitlity	SuperSign Lite/Simple Editor/W	
	Headphone Out		
Interface (Set Side)	HDMI In	1 (1.4)	
miceriace (See Side)	USB	2 (2.0)	
	CI Slot	1	
	RF In	2	
	AV In	1 (Share with Component)	
	Full Scart	-	
	Component In (Y, Pb, Pr-Video)	1 (RCA5 Type)	
	Digital Audio Out (Coaxial / Optical)	1 (Optical)	
	HDMI / HDCP Input	2 (1.4)	
	USB	-	
	RGB In (D-sub 15pin) - PC	1	
Interface (Set Rear)	PC Audio Input	1 (Share with Component Audio)	
	RS-232C (D-Sub 9pin)	1 (Phone Jack Type, Control & Service)	
	Headphone Out	1	
	Clock Interface (D-sub 15pin)	-	
	RJ45 (Usage Purpose)	1 (Ethernet)	
	External Speaker Out (3.5mm Phone Jack)	1 (Spk-out 1)	
	TV link Configuration (Phone Jack Type)		
	Debug (Phone Jack Type)	1 (Service)	
	Anti-theft System	Kensington Lock	
	And their System		
	W x H x D / Weight (with stand)	43" : 974 x 625 x 220 / 9.3	
Dimension	Unit: mm / kg	49" : 1,107 x 701 x 235 / 11.4	
	one.min/ kg	55" : 1,241 x 775 x 216 / 16.6	
	Voltage, Hz	100 ~ 240V, 50 / 60Hz	
	voicage, i iz		
Power		43" : 75.0	
	Typical (Watts)	49" :81.5	
		55" :109	

	WCD DIOWSCI		
Smart Feature	Pre-loaded App	-	-
	Soft AP	-	_
	Screen Share		
	Smart Share		_
	Bluetooth Sound Sync / LG Sound Sync		
	EzManager (Simplicity)		
Easy Installation	USB Cloning		•
	Wake on RF		
	WOL (Wake On LAN)		
	SNMP		
	Diagnostics	• (Self Diagnostics(USB))	• (Self Diagnostics(USB))
Management	TVLink Interactive	-	-
	HTNG/HDMI-CEC	• (1.4) / • (1.3)	• (1.4) / • (1.3)
	IR Out	• (RS-232C)	• (RS-232C)
	Multi IR Code	•	• (1.5 2520)
	Welcome Screen / Video	• / •	• / •
	One Channel Map	•	•
	External Speaker Out	•	
	Instant ON		
Hospitality Features	External Power		
	External Clock Compatibility	-	
	USB Auto playback / USB Auto playback+	• / •	• / •
	Anti-theft Dongle Cover		
	Crestron Certified Compatibility		
	Time Scheduler / First Use	• / -	• / -
Signage Features	RTC (Real Time Clock)		-
Signage reacures	NTP Sync Timer		
	SuperSign SW Compatibitlity		
	Headphone Out		
	HDMI In	1 (1.3)	
Interface (Set Side)	USB	1 (2.0)	
	CI Slot	1	1
	RF In	2	2
	AVIn		1 (Share with Component)
	Full Scart		(Share with Component)
	Component In (Y, Pb, Pr-Video)	 1 (RCA5 Type)	 1 (RCA5 Type)
Interface (Set Rear)	Digital Audio Out (Coaxial / Optical)	1 (Optical)	- (NCAS Type)
	HDMI / HDCP Input	1 (1.3)	1 (1.4)
	USB	1 (1.5)	1 (2.0)
	RGB In (D-sub 15pin) - PC		- (2.0)
	PC Audio Input	1 (Share with Component Audio)	
	RS-232C (D-Sub 9pin)	1 (Control & Service)	1 (Control & Service)
	Headphone Out	(Control & Service)	1 (Control & Service)
	Clock Interface (D-sub 15pin)		
	RJ45 (Usage Purpose)	1	1 (MHEG&Service)
	External Speaker Out (3.5mm Phone Jack)		1 (IVII ILUXSEI VICE)
	TV link Configuration (Phone Jack Type)	1 (Spk-out 1)	<u>-</u>
	Debug (Phone Jack Type)		<u>-</u>
	Anti-theft System	- Vancington Lock	
	And-dient System	Kensington Lock	Kensington Lock
Dimension	W x H x D / Weight (with stand) Unit : mm / kg	24":556 x 384.3 x 140.6 / 3.7 28":641.5 x 430 x 175 / 4.9	32" : 728 x 475 x 181.1 / 5.0 43" : 970 x 624 x 220.4 / 8.4 49" : 1,108 x 707 x 217.9 / 10.9

100 ~ 240V, 50 / 60Hz

24" : 29.8 28" : 36.2

EU

LW341C

24" / 28"

1,366 x 768 (HD)

DVB-T2/C/S2

5W + 5W / 2.0 CH

Size

Panel

HDR

Broadcasting System

Hospitality Solution Quick Menu

Audio Output / Speaker System

Resolution

DRM webOS Web Browser

Pro:Centric® Type

Voltage, Hz

Typical (Watts)

Power

EU / CIS

LV300C

32H" / 43" / 49"

43" / 49" : 1,920 x 1,080 (FHD) 32" : 1,366 x 768 (HD)

DVB-T2/C/S2

5W + 5W / 2.0 CH

100 ~ 240V, 50 / 60Hz

32":40.5 43":50 49":51